

## Sealprem PCL Tape

### 1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

#### 1.1 Product Name

Sealprem PCL Tape all colours

### 2. Use

An entry level cloth duct tape characterised by good tensile strength and a considerable adhesion that make it suitable for multiple daily emergency repairs with different materials and surfaces. Sealprem PCL Tape is a lightly conformable, water resistant, and easy to use multipurpose tape.

This adhesive tape is designed to be applied semi permanently without clean removal, can be used as protection and sealant in many contexts like home, construction sites, Industrial interventions and even agricultural activities.

CHARACTERISTICS	UNITS	STD. VALUES	TOLER	TEST METHOD
Total Weight	g/m2	110	± 10%	ISO 536
Total Thickness	µm	140	± 10%	AFERA 5006
MD tensile strength	N/cm	> 28		AFERA 5004
MD elongation at break	%	> 10		AFERA 5004
Adhesion to steel plate	N/cm	> 5,5		AFERA 5001
Rolling ball tack		<0,5		PSTC 6

Available colours: SILVER - BLACK - WHITE - RED - ORANGE - YELLOW - DARK BROWN- GREEN - BLUE- DARK OLIVE GREEN

Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice.

All information has to be intended as generic advice for the use of products. Users have to verify the suitability of each tape in actual application under specific conditions.

### 3. Supplier Information

**Premier Sealant Systems Ltd.**

T 01724 864 100 | E [sales@sealprem.com](mailto:sales@sealprem.com) | [www.sealprem.com](http://www.sealprem.com)

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: 19 Titan Court, Luton, LU4 8LL | Registered in Cardiff No. 3000843

Premier Sealant Systems Ltd., Mercia Way, Foxhills Industrial Park, Scunthorpe, North  
Lincolnshire, DN15 8RE  
T: 01724 864 100

#### 4. Terms & Conditions of liability

Tapes must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 15 to 25°C with max. Relative humidity of 60%.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 10°C. With a storage temperature lower than 10°C, it is always suggested temperature reconditioning of the tape at room temperature (15°C - 25 ° C) before its use.

Shelf life from date of manufacture: (No yellowing and < 10% loss in performance at 23 °C, 50 % humidity) is considered 12 months for Slit rolls and 6 for Jumbo rolls.

PPM does not take responsibility for the defective material is not stored and used in accordance with the conditions listed above.

**Premier Sealant Systems Ltd.**

T 01724 864 100 | E [sales@sealprem.com](mailto:sales@sealprem.com) | [www.sealprem.com](http://www.sealprem.com)

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: 19 Titan Court, Luton, LU4 8LL | Registered in Cardiff No. 3000843